

Type	RENMY2	RENMY4	RENLY2	REMY2	REMY4
Appearance					
Dimensions(L×W×H)mm	27.5×21×35	27.5×21×35	27.5×21×35	27.5×21×36	27.5×21×36
Contact form	2c	4c	2c,2a,2b	2c	4c
Rated load	5A 250VAC/30VDC	5A 250VAC/30VDC	10A 250VAC/30VDC	5A 250VAC/28VDC	5A 250VAC/28VDC
Contact resistance	≤50MΩ	≤50MΩ	≤50MΩ	≤50MΩ	≤50MΩ
Coil voltage	DC	6-110V	6-110V	6-110V	6-110V
	AC	6-240V	6-240V	6-240V	6-240V
Coil power	0.9W/1.2VA	0.9W/1.2VA	0.9W/1.2VA	0.9W/1.2VA	0.9W/1.2VA
Coil & contacts	1500VAC/1min	1500VAC/1min	1500VAC/1min	1500VAC/1min	1500VAC/1min
Contacts & contacts	1000VAC/1min	1000VAC/1min	1000VAC/1min	1000VAC/1min	1000VAC/1min
Insulation resistance	≥100MΩ	≥100MΩ	≥100MΩ	≥100MΩ	≥100MΩ
Electrical life	10 ⁵	10 ⁵	10 ⁵	10 ⁵	10 ⁵
Mechanical life	10 ⁷	10 ⁷	10 ⁷	10 ⁷	10 ⁷
Operating temperature	-40~+70℃	-40~+70℃	-40~+70℃	-40~+70℃	-40~+70℃
Weight(g)	35g	38g	35g	38g	38g
Terminal layout					
Mounting holes (mm)					

Type	RELY2	REXMY2	REXMY4	MY2	MY4
Appearance					
Dimensions(L×W×H)mm	27.5×21×36	27.5×21×36	27.5×21×36	27.5×21×36	27.5×21×36
Contact form	2c	4c	2c	4c	2c
Rated load	10A 250VAC/28VDC	5A 250VAC/28VDC	5A 250VAC/28VDC	5A 250VAC/28VDC	5A 250VAC/28VDC
Contact resistance	≤50MΩ	≤50MΩ	≤50MΩ	≤50MΩ	≤50MΩ
Coil voltage	DC	6-110V	6-110V	6-110V	6-110V
	AC	6-240V	6-240V	6-240V	6-240V
Coil power	0.9W/1.2VA	0.9W/1.2VA	0.9W/1.2VA	0.9W/1.2VA	0.9W/1.2VA
Coil & contacts	1500VAC/1min	1500VAC/1min	1500VAC/1min	1000VAC/1min	1000VAC/1min
Contacts & contacts	1000VAC/1min	1000VAC/1min	1000VAC/1min	1000VAC/1min	1000VAC/1min
Insulation resistance	≥100MΩ	≥100MΩ	≥100MΩ	≥100MΩ	≥100MΩ
Electrical life	10 ⁵	10 ⁵	10 ⁵	10 ⁵	10 ⁵
Mechanical life	10 ⁷	10 ⁷	10 ⁷	10 ⁷	10 ⁷
Operating temperature	-40~+70℃	-40~+70℃	-40~+70℃	-40~+70℃	-40~+70℃
Weight(g)	38g	38g	38g	38g	38g
Terminal layout					
Mounting holes (mm)					